Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources			o 13 With regula to energ	B)			
Supplier's name or trade mark: Paulmann Supplier's address: Info, Quezinger Feld 2, 31832 Springe-Völksen, DE							
							Model identifier: 28773
Type of light so	urce:						
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS			
Light source cap-type		E27					
(or other electric interface)							
Mains or non-m	nains:	MLS	Connected light source (CLS):	No			
Colour-tuneable light source:		No	Envelope:	-			
High luminance light source:		No					
Anti-glare shield:		No	Dimmable:	Yes			
		Product para					
Parameter		Value	Parameter	Value			
Enorgy consur	mntion in on	General product p		г			
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		5	Energy efficiency class	F			
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		470 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700			
On-mode power (P _{on}), ex- pressed in W		5,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	84			
Outer dimen-	Height	145	Spectral power dis-	See image			
sions without separate con- trol gear, light- ing control	Width Depth	95 95	tribution in the range 250 nm to 800 nm, at full-load	in last page			

parts and non- lighting con- trol parts, if any (millime-						
tre) Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	40			
		Chromaticity coordinates (x and y)	0,466 0,419			
Parameters for LED and OLED light sources:						
R9 colour rendering index va	lue 8	Survival factor	-			
the lumen maintenance factor	or -					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,62	Colour consistency in McAdam ellipses	6			
Claims that an LED light sour replaces a fluorescent lig source without integrated by last of a particular wattage.	ght	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	0,3	Stroboscopic effect metric (SVM)	0,3			

(a)'-': not applicable; (b)'-': not applicable;

