## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Brilliant

Supplier's address: Customer Service, Brilliantstraße 1, 27442 Gnarrenburg, DE

## Model identifier: G30534/13

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	/					
(or other electric interface)						
Mains or non-mains:	NMLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	No			
Product parameters						

Parameter		Value	Parameter	Value		
General product parameters:						
Energy consum mode (kWh/10 up to the neares	00 h), rounded	13	Energy efficiency class	F		
dicating if it refe a sphere (360°)	s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	1 500 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	2 700		
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	13,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82		
Outer dimen-	Height	1	Spectral power dis-	See image		
sions without	Width	309	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	6	range 250 nm to 800 nm, at full-load	Deco 1 /		

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	Yes	lf yes, equivalent power (W)	105			
		Chromaticity coordi-	0,456			
		nates (x and y)	0,409			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	7	Survival factor	0,96			
the lumen maintenance factor	0,97					

(a)'-' : not applicable;

(b)<sub>'-'</sub> : not applicable;

