Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Customer Services, AGP Trading B.V. P.O. Box 39, 6001 GT Weert, The

Netherlands

Model identifier: S8857

Type	of light	source:
------	----------	---------

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	B22		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Product parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
Energy consur mode (kWh/10 up to the neare	00 h), rounded	5	Energy efficiency class	F	
indicating if it re in a sphere (3)	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	470 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700	
On-mode pexpressed in W	oower (P _{on}),	4,9	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80	
Outer	Height	101	Spectral power	See image	
dimensions	Width	60	distribution in the	in last page	

without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	60	range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	40		
		Chromaticity coordinates (x and y)	0,458		
Parameters for LED and OLED light sources:					
R9 colour rendering index val	ue 0	Survival factor	0,90		
the lumen maintenance factor	or 0,93				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,00	Colour consistency in McAdam ellipses	6		
Claims that an LED lig source replaces a fluoresce light source without integrat ballast of a particular wattage	ed	If yes then replacement claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9		

(a)'-': not applicable; (b)'-': not applicable;

