## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| sources  |                 | 27.11314 (23) 2313) 2        | ors with regard to energ   | by labelling of light |  |  |
|--|-----------------|------------------------------|--|-----------------------|--|--|
| Supplier's name or trade mark: Hama  |                 |                              |  |                       |  |  |
| Supplier's address: Produktmanagement, Dresdner Strasse 9, 86653 Monheim, DE   |                 |                              |  |                       |  |  |
| Model identifie  | r: 00176560     |                              |  |                       |  |  |
| Type of light so   | urce:           |                              |  |                       |  |  |
| Lighting techno  | logy used:      | LED                          | Non-directional or directional:  | NDLS                  |  |  |
| Light source cap-type (or other electric interface)  |                 | Wired                        |  |                       |  |  |
| Mains or non-mains:  |                 | MLS                          | Connected light source (CLS):  | Yes                   |  |  |
| Colour-tuneable  | e light source: | Yes                          | Envelope:  | -                     |  |  |
| High luminance light source:   |                 | No                           |  |                       |  |  |
| Anti-glare shield:   |                 | No                           | Dimmable:  | No                    |  |  |
| Product parameters   |                 |                              |  |                       |  |  |
| Parameter  |                 | Value                        | Parameter  | Value                 |  |  |
| General product parameters:  |                 |                              |  |                       |  |  |
| Energy consumption in on-<br>mode (kWh/1000 h), rounded<br>up to the nearest integer   |                 | 18                           | Energy efficiency class  | F                     |  |  |
| Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) |                 | 1 500 in Wide<br>cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 27006500              |  |  |
| On-mode power (P <sub>on</sub> ), expressed in W   |                 | 18,0                         | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal  | 0,34                  |  |  |
| Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal                                |                 | 0,34                         | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 80                    |  |  |
| Outer  | Height          | 100                          | Spectral power   | See image             |  |  |
| dimensions   | Width           | 300                          | distribution in the  | in last page          |  |  |
| without  | Depth           | 300                          |  | Page 1 / 3            |  |  |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)                      |      | range 250 nm to 800<br>nm, at full-load |       |  |  |  |
|---|------|---|-------|--|--|--|
| Claim of equivalent power <sup>(a)</sup>  | -    | If yes, equivalent power (W)            | -     |  |  |  |
|   |      | Chromaticity coordinates (x and y)      | 0,310 |  |  |  |
| Parameters for LED and OLED light sources:  |      |   |       |  |  |  |
| R9 colour rendering index value   | 6    | Survival factor                         | 0,90  |  |  |  |
| the lumen maintenance factor  | 0,80 |   |       |  |  |  |
| Parameters for LED and OLED mains light sources:  |      |   |       |  |  |  |
| displacement factor (cos φ1)  | 0,51 | Colour consistency in McAdam ellipses   | 2     |  |  |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | _(b) | If yes then replacement claim (W)       | -     |  |  |  |
| Flicker metric (Pst LM)   | 0,0  | Stroboscopic effect<br>metric (SVM)     | 0,0   |  |  |  |

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

## Spectra

