## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LED line®  Supplier's address: Product Menager, Dębowa 1 07-410 Tobolice Mazowieckie Rzekuń Polska											
							Model identifie	er: 248146			
							Type of light so	urce:			
Lighting techno	logy used:	LED	Non-directional or directional:	DLS							
Light source cap-type MR11											
(or other electri	ic interface)										
Mains or non-m	Mains or non-mains:		Connected light source (CLS):	No							
Colour-tuneable	e light source:	No	Envelope:	-							
High luminance	light source:	No									
Anti-glare shield:		No	Dimmable:	No							
Product parameters											
Parameter		Value	Parameter	Value							
General product parameters:											
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		3	Energy efficiency class	G							
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		200 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000							
On-mode power (P <sub>on</sub> ), expressed in W		3,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00							
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80							
Outer	Height	35	Spectral power	See image							
dimensions	Width	35	distribution in the	in last page							
without	Depth	36									

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,380			
Parameters for directional light sources:						
Peak luminous intensity (cd)	407	Beam angle in degrees, or the range of beam angles that can be set	38			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	7	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

