## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources					
Supplier's name	or trade mark:	OSRAM			
Supplier's addre	ess: LEDVANCE G	mbH, Parkring 33, 0	Garching, Germany		
Model identifier	r: AC34085				
Type of light sou	ırce:				
Lighting technology used:		other FL	Non-directional or directional:	NDLS	
Light source cap-type		G5			
(or other electric interface)					
Mains or non-mains:		NMLS	Connected light source (CLS):	No	
Colour-tuneable light source:		No	Envelope:	-	
High luminance light source:		No			
Anti-glare shield:		No	Dimmable:	Yes	
Product parameters					
Parameter		Value	Parameter	Value	
		General product p	T		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		14	Energy efficiency class	G	
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		830 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000	
On-mode power (P <sub>on</sub> ), expressed in W		13,2	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00	
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	60	
Outer dimensions	Height	531	Spectral power	See image	
	Width	16	distribution in the	in last page	
without	Depth	16		Page 1/	

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>	- If yes, equivalent power (W)	-
	Chromaticity coordinates (x and y)	0,380 0,394

(a)'-': not applicable; (b)'-': not applicable;

