Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

| sources | PELLOATED REGOT | -AITON (LO) 2019/2 | ots with regard to energ | gy labelling of light | |
|--|---------------------------|-------------------------|--|-----------------------|--|
| Supplier's name | e or trade mark: | OSRAM | | | |
| Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany | | | | | |
| Model identifie | er: AC34259 | | | | |
| Type of light so | urce: | | | | |
| Lighting techno | logy used: | CFLni | Non-directional or directional: | NDLS | |
| Light source cap-type (or other electric interface) | | G23 | | | |
| Mains or non-mains: | | NMLS | Connected light source (CLS): | No | |
| Colour-tuneable | e light source: | No | Envelope: | - | |
| High luminance light source: | | No | | | |
| Anti-glare shield | d: | No | Dimmable: | No | |
| Product parameters | | | | | |
| Parameter | | Value | Parameter | Value | |
| | | General product p | | I | |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | | 8 | Energy efficiency class | G | |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 400 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700 | |
| On-mode pexpressed in W | oower (P _{on}), | 7,1 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 | |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 80 | |
| Outer | Height | 136 | Spectral power | See image | |
| dimensions | Width | 12 | distribution in the | in last page | |
| without | Depth | 12 | | Page 1 / 3 | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | range 250 nm to 800 nm, at full-load | |
|--|--------------------------------------|----------------|
| Claim of equivalent power ^(a) | - If yes, equivalent power (W) | - |
| | Chromaticity coordinates (x and y) | 0,455 0,415 |

(a)'-': not applicable; (b)'-': not applicable;

