## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LEDVANCE Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany										
						Model identifie	er: AC33856			
						Type of light so	urce:			
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS						
Light source cap	Light source cap-type G13									
(or other electri	ic interface)									
Mains or non-m	nains:	NMLS	Connected light source (CLS):	No						
Colour-tuneable		No	Envelope:	-						
High luminance	light source:	No								
Anti-glare shield:		No	Dimmable:	No						
Product parameters										
Parameter		Value	Parameter	Value						
General product parameters:										
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		9	Energy efficiency class	D						
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1 100 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500						
On-mode power (P <sub>on</sub> ), expressed in W		7,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00						
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	83						
Outer	Height	603	Spectral power	See image						
dimensions without	Width	27	distribution in the	in last page						
vvitilout	Depth	27								

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity	0,312			
		coordinates (x and y)	0,328			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,70					

(a)'-': not applicable; (b)'-': not applicable;

