Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: PHILIPS

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

Model identifier: 8718696814710

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type	GU5.3		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
•.	mption in on- 100 h), rounded st integer	7	Energy efficiency class	F		
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	621 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode p expressed in W	oower (P _{on}),	7,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
for CLS, expres	idby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer	Height	45	Spectral power	See image		
dimensions	Width	51	distribution in the	in last page		
without	Depth	51]	Page 1/3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load					
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	50				
		Chromaticity coordinates (x and y)	0,458				
Parameters for directional light sources:							
Peak luminous intensity (cd)	1 400	Beam angle in degrees, or the range of beam angles that can be set	36				
Parameters for LED and OLED light sources:							
R9 colour rendering index value	0	Survival factor	0,90				
the lumen maintenance factor	0,93						

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

