Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	PHILIPS

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL
--

Model identifier: 92	.90020270
----------------------	-----------

_	•			
Ivpe	Ot	light	source	j:

LED	Non-directional or directional:	NDLS
E14		
MLS	Connected light source (CLS):	No
No	Envelope:	-
No		
No	Dimmable:	No
	E14 MLS No No	MLS Connected light source (CLS): No Envelope: No

Product parameters

Parameter		Value	Value Parameter	
General product parameters:				
<u> </u>	mption in on- 100 h), rounded st integer	5	Energy efficiency class	F
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	470 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode pressed in W	oower (P _{on}),	4,3	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
for CLS, expres	dby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	97	Spectral power	See image
dimensions	Width	35	distribution in the	in last page
without	Depth	35		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	40
		Chromaticity coordinates (x and y)	0,380
Parameters for LED and OLED lig	ht sources:		
R9 colour rendering index value	1	Survival factor	0,90
the lumen maintenance factor	0,93		
Parameters for LED and OLED mains light sources:			
displacement factor (cos φ1)	0,51	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

