Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources				
Supplier's name or trade mark: PHILIPS				
Supplier's address: Customer Car	e Philips, I.B.R.S	S./C.C.R.I. /Numéro 10461, 560	00VB Eindhoven, NL	
Model identifier: 9290020550				
Type of light source:				
Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	E27			
(or other electric interface)				
Mains or non-mains:	MLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	No	
	Product pa	arameters		
	_		_	

Parameter Value Parameter Value **General product parameters:** Energy consumption in on-17 Energy efficiency D mode (kWh/1000 h), rounded class up to the nearest integer Useful luminous flux (фuse), 2 452 in Correlated 2 700 colour indicating if it refers to the flux Sphere (360°) temperature, in a sphere (360°), in a wide rounded to the cone (120º) or in a narrow cone nearest 100 Κ, (90°) or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode $(P_{on}),$ 17,0 Standby power (P_{sb}) , 0,00 power expressed in W expressed and rounded to the second decimal Networked standby power (P_{net}) Colour 80 rendering index, rounded to for CLS, expressed in W and the nearest integer, rounded to the second decimal or the range of CRIvalues that can be set 121 Spectral See image Outer Height power dimensions distribution in the in last page 70 Width without

70

Depth

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load		
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	150	
		Chromaticity coordinates (x and y)	0,458	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	0	Survival factor	0,90	
the lumen maintenance factor	0,93			
Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)	0,71	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4	

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

