## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SEBSON	
---------------------------------------	--

Supplier's address: Support, SEBSON, Gernotstr. 17, 44319 Dortmund, Germany

Model identifier: MR11\_SMD12

Tvi	рe	of	lig	ht	SO	urce	:
. , ,		•	о		-		•

Type of light so	urce:				
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS	
Light source cap	o-type	GU4 / MR 11			
(or other electr	ic interface)				
Mains or non-m	nains:	NMLS	Connected light source (CLS):	No	
Colour-tuneable	e light source:	No	Envelope:	-	
High luminance	light source:	No			
Anti-glare shield	d:	No	Dimmable:	No	
		Product para	meters		
Parameter		Value	Parameter	Value	
		General product	parameters:		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		2	Energy efficiency class	F	
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		150 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 900	
On-mode power (P <sub>on</sub> ), expressed in W		1,6	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00	
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80	
Outer	Height	36	Spectral power	See image	
dimensions	Width	35	distribution in the	in last page	
without	Depth	35			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-				
		Chromaticity coordinates (x and y)	0,422				
Parameters for LED and OLED light sources:							
R9 colour rendering index value	4	Survival factor	0,90				
the lumen maintenance factor	0,90						

(a)'-': not applicable; (b)'-': not applicable;

