Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	SEBSON

	Supplier's address:	Support, SEBSON	, Gernotstr. 17	, 44319 Dortmund,	. Germany
--	---------------------	-----------------	-----------------	-------------------	-----------

Model i	dentifier:	E14	P45	6W	RA97

_	•			
Type	Λt	liaht	COLL	rca.
IVDE	VI.	HEIIL	SOUI	LC.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E14		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter		Value	Parameter	Value	
General product parameters:					
0,	mption in on- 200 h), rounded est integer	6	Energy efficiency class	G	
indicating if it in a sphere (3	us flux (φuse), refers to the flux 660º), in a wide in a narrow cone	400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000	
On-mode expressed in W	power (P _{on}),	6,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00	
for CLS, expre	ndby power (P _{net}) essed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	97	
Outer	Height	84	Spectral power	See image	
dimensions	Width	46	distribution in the	in last page	
without	Depth	46			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,437
Parameters for LED and OLED lig	ht sources:		
R9 colour rendering index value	90	Survival factor	0,90
the lumen maintenance factor	0,90		
Parameters for LED and OLED m	ains light sources:		
displacement factor (cos φ1)	0,52	Colour consistency in McAdam ellipses	1
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

