Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SEBSON				
upplier's address: Support, Adress: SEBSON, Gernotstr. 17, 44319 Dortmund, German	y			

Model identifier:	G4LT	SMD12

Type of light source:				
Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	G4			
(or other electric interface)				
Mains or non-mains:	NMLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	No	
Product narameters				

Anti-glare shield: No Dimmable: No Product parameters Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide No Dimmable: No Parameter Value General product parameters: Energy efficiency class Correlated colour 2 900 temperature, rounded to the

up to the neare	st integer			
indicating if it r in a sphere (3	us flux (фuse), refers to the flux 60º), in a wide n a narrow cone	200 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 900
On-mode pressed in W	oower (P _{on}),	2,5	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
for CLS, expre	ndby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	41	Spectral power distribution in the	See image
dimensions	Width	30		in last page
without	Depth	30		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load		
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,432	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	3	Survival factor	0,90	
the lumen maintenance factor	0,90			

(a)'-': not applicable; (b)'-': not applicable;

