## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources								
Supplier's name or trade mark: Twinkly								
Supplier's address: Info Twinkly, Via Tortona 37 , 20144 Milano, IT								
Model identifier: TWFL200STW-WUK								
Type of light so	urce:							
Lighting technology used:		LED	Non-directional or directional:	NDLS				
Light source cap-type		Wire						
(or other electric interface)								
Mains or non-mains:		NMLS	Connected light source (CLS):	Yes				
Colour-tuneable light source:		Yes	Envelope:	-				
High luminance light source:		No						
Anti-glare shield:		No	Dimmable:	Only with specific dimmers				
Product parameters								
Parameter		Value	Parameter	Value				
General product parameters:								
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		18	Energy efficiency class	G				
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		116 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	15 440				
On-mode power (P <sub>on</sub> ), expressed in W		18,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,46				
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		0,46	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	45				
Outer	Height	2 000	Spectral power	See image				
dimensions	Width	20	distribution in the	in last page				

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	10	range 250 nm to 800 nm, at full-load			
Claim of equivalent power <sup>(a)</sup>		-	If yes, equivalent power (W)	-		
			Chromaticity	0,254		
			coordinates (x and y)	0,276		
Parameters for LED and OLED light sources:						
R9 colour rendering index value		0	Survival factor	0,90		
the lumen maintenance factor		0,93				

(a)'-': not applicable;

(b)<sub>'-'</sub> : not applicable;