Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	LLLOATED REGOL	ATION (LO) 2013/20	U15 with regard to ener	gy labelling of light			
Supplier's name	or trade mark:	ledscom.de					
Supplier's address: LEDs Com GmbH, Dohrweg 2a, Mönchengladbach, DE							
Model identifier	: LC-SS-615-WW	I					
Type of light sou	ırce:						
Lighting technology used:		LED	Non-directional or directional:	NDLS			
Light source cap-type		E27					
(or other electric interface)							
Mains or non-mains:		MLS	Connected light source (CLS):	No			
Colour-tuneable light source:		No	Envelope:	-			
High luminance light source:		No					
Anti-glare shield:		No	Dimmable:	No			
		Product para	meters				
Parameter		Value	Parameter	Value			
		General product p	T	I			
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		4	Energy efficiency class	D			
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		550 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700			
On-mode power (P _{on}), expressed in W		4,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,50			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80			
Outer	Height	170	Spectral power	See image			
dimensions	Width	125	distribution in the	in last page			
without	Depth	125		Page 1			

separate control gear, lighting control parts and non- lighting control parts,			range 250 nm to 800 nm, at full-load				
if any (millimetre)							
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-			
			Chromaticity coordinates (x and y)	0,464 0,421			
Parameters for	LED and OLED lig	ht sources:					
R9 colour rendering index value		14	Survival factor	0,90			
the lumen maintenance factor		0,94					
Parameters for LED and OLED mains light sources:							
displacement factor (cos φ1)		0,00	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)		1,0	Stroboscopic effect metric (SVM)	0,9			

(a)'-': not applicable;

(b)_{'-'} : not applicable;

