Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ledscom.de

Supplier's address: LEDs Com GmbH, Dohrweg 2a, Mönchengladbach, DE

Model identifier: LC-SS-605-WW

Type of light source:

Colour-tuneable light source: High luminance light source:	No No	Envelope:	-
		source (CLS):	
(or other electric interface) Mains or non-mains:	MLS	Connected light	No
Light source cap-type	E27		
Lighting technology used:	LED	Non-directional or directional:	NDLS

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
•.	mption in on- 200 h), rounded est integer	5	Energy efficiency class	E		
indicating if it in a sphere (3	us flux (φuse), refers to the flux 860º), in a wide in a narrow cone	461 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode expressed in W	power (P _{on}),	4,1	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,50		
for CLS, expre	ndby power (P _{net}) essed in W and e second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer	Height	105	Spectral power	See image		
dimensions	Width	60	distribution in the	in last page		
without	Depth	60	1	Page 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,470			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	9	Survival factor	0,90			
the lumen maintenance factor	0,94					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,00	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9			

(a)'-' : not applicable;

(b)'_-' : not applicable;

